



Malzeme : Özel Alaşımli Çelik 1.2516

Sertlik : Gövde 60/62 HRC / Kafa 45+5 HRC

Yüzey : Sertleştirilmiş, taşlanmış

d1 h6	d2	d3	K +0,2	L+2								
				80	100	125	160	200	250	315		
1	1,8	d1 +0,03	0,5	*	*	*	*	*	*	*	*	
1,1				*	*	*	*	*	*	*	*	*
1,2	2,0			*	*	*	*	*	*	*	*	*
1,3				*	*	*	*	*	*	*	*	*
1,4	2,2			*	*	*	*	*	*	*	*	*
1,5				*	*	*	*	*	*	*	*	*
1,6	2,5			*	*	*	*	*	*	*	*	*
1,7				*	*	*	*	*	*	*	*	*
1,8	2,8			*	*	*	*	*	*	*	*	*
1,9				*	*	*	*	*	*	*	*	*
2,0	3,0			*	*	*	*	*	*	*	*	*
2,1				*	*	*	*	*	*	*	*	*
2,2	3,2			*	*	*	*	*	*	*	*	*
2,3				*	*	*	*	*	*	*	*	*
2,4	3,5			*	*	*	*	*	*	*	*	*
2,5				*	*	*	*	*	*	*	*	*
2,6	4,0			*	*	*	*	*	*	*	*	*
2,7				*	*	*	*	*	*	*	*	*
2,8	4,0	*	*	*	*	*	*	*	*	*		
2,9		*	*	*	*	*	*	*	*	*		
3,0	4,5	*	*	*	*	*	*	*	*	*		
3,1		*	*	*	*	*	*	*	*	*		
3,2	4,5	*	*	*	*	*	*	*	*	*		
3,3		*	*	*	*	*	*	*	*	*		
3,4	5,0	*	*	*	*	*	*	*	*	*		
3,5		*	*	*	*	*	*	*	*	*		
3,6	5,0	*	*	*	*	*	*	*	*	*		
3,7		*	*	*	*	*	*	*	*	*		
3,8	5,5	*	*	*	*	*	*	*	*	*		
3,9		*	*	*	*	*	*	*	*	*		
4,0	5,5	*	*	*	*	*	*	*	*	*		
4,1		*	*	*	*	*	*	*	*	*		
4,2	6,0	*	*	*	*	*	*	*	*	*		
4,3		*	*	*	*	*	*	*	*	*		
4,4	6,0	*	*	*	*	*	*	*	*	*		
4,5		*	*	*	*	*	*	*	*	*		
4,6	6,5	*	*	*	*	*	*	*	*	*		
4,7		*	*	*	*	*	*	*	*	*		
4,8	6,5	*	*	*	*	*	*	*	*	*		
4,9		*	*	*	*	*	*	*	*	*		
5,0	7,0	*	*	*	*	*	*	*	*	*		
5,1		*	*	*	*	*	*	*	*	*		
5,2	7,0	*	*	*	*	*	*	*	*	*		
5,3		*	*	*	*	*	*	*	*	*		
5,4	8,0	*	*	*	*	*	*	*	*	*		
5,5		*	*	*	*	*	*	*	*	*		
5,6	9,0	*	*	*	*	*	*	*	*	*		
5,7		*	*	*	*	*	*	*	*	*		
5,8	9,0	*	*	*	*	*	*	*	*	*		
5,9		*	*	*	*	*	*	*	*	*		
6,0	10,0	*	*	*	*	*	*	*	*	*		
6,5		*	*	*	*	*	*	*	*	*		
7,0	11,0	*	*	*	*	*	*	*	*	*		
7,5		*	*	*	*	*	*	*	*	*		
8,0	12,0	*	*	*	*	*	*	*	*	*		
8,5		*	*	*	*	*	*	*	*	*		
9,0	13,0	*	*	*	*	*	*	*	*	*		
9,5		*	*	*	*	*	*	*	*	*		
10,0	14,0	*	*	*	*	*	*	*	*	*		
10,5		*	*	*	*	*	*	*	*	*		
11,0	15,0	*	*	*	*	*	*	*	*	*		
12,0		*	*	*	*	*	*	*	*	*		
13,0	16,0	*	*	*	*	*	*	*	*	*		
14,0		*	*	*	*	*	*	*	*	*		
16,0	18,0	*	*	*	*	*	*	*	*	*		

